Note: Due to the age of this e-newsletter, some of the links have been disabled. Please contact marketing@multi-conv.com if you would like specific information on any information inside of this archived message.



Call for a Quote: 1-800-236-7960



Pneumatic 90° Push Transfer for Many Applications

Leading this meat package from the narrow edge upstream then transferring to lead from the wide edge downstream. Very nifty!

<u>Multi-Conveyor</u> recently built the pneumatic 90° transfer in the <u>video</u> found on our <u>Pneumatics & Devices page</u> on our website. It was designed for a packaged meat operation that required products that are two or three abreast to be transferred at 90 degrees at 20 cycles per minute.

This application required a change in orientation not only from narrow edge leading from the upstream equipment to wide edge leading for the downstream equipment, but also needed to combine the three lanes to a single flow. Both of these requirements were fulfilled with the box-in-box style pneumatic pusher design.

The design results in the elimination of pinch points associated with the mechanism itself, and care is also taken to avoid pinch points associated with the adjacent guide rails.

Also considered in the design of the unit were the <u>sanitation</u> and cleanability of the mechanism. The adjacent rails and the product end stop are easily removable. The stainless steel cover over the assembly can be removed for access to the easily removable air cylinder and UHMW slide guides.



A note to all of our friends in Canada:

The Canada Anti-Spam Law will take effect on July 1, 2014.

If you have received this message, your e-mail is currently in our database at your consent. If you no longer wish to receive monthly updates from Multi-Conveyor, and in accordance with the new Anti-Spam law, please "Unsubscribe" at the bottom of this message.

If you wish to continue to receive the latest news, technology updates and brief messages from Mult-Conveyor, you need not respond or take any action. We will then assume that we have your permission to continue to send updates to your e-mail address.

We would ike to take this opportunity to thank you all for being a part of our audience and we hope to continue to serve your conveying needs and news for years to come.

The pneumatic 90° push transfer used for these irregular shaped products with uneven wraps can also be used for traditional carton and case handling applications. The pusher can be custom designed for various product sizes, weights and rates, as well as for the particular environment associated with the application.

Construction can be <u>stainless steel</u> (11 gauge standard) or <u>painted carbon steel</u>, with standard duty components or sanitary wash down duty components as needed.

Call today! 1-800-236-7960

Multi-Conveyor...
your best, conveyed better.



Note: Due to the age of this e-newsletter, some of the links have been disabled. Please contact marketing@-multi-conv.com if you would like specific information on the content or videos inside of this archived message.

Find all of our videos at:

http://www.multi-conveyor.com/multi-media-center/videos